

# Типове II: Шаблони на функции. Указатели към функции

Калин Георгиев

15 януари 2016 г.

## Шаблони (на функции)

# Еднообразни функции за различни типове

```

int findIndexMax
    (int arr[], int arrSize)
{
    int indexMax = 0;
    for (int i = 1; i < arrSize; i++)
        if (arr[indexMax] < arr[i])
            indexMax = i;

    return indexMax;
}

int findIndexMax
    (char arr[], int arrSize)
{
    int indexMax = 0;
    for (int i = 1; i < arrSize; i++)
        if (arr[indexMax] < arr[i])
            indexMax = i;

    return indexMax;
}

```

```

int findIndexMax
    (double arr[], int arrSize)
{
    int indexMax = 0;
    for (int i = 1; i < arrSize; i++)
        if (arr[indexMax] < arr[i])
            indexMax = i;

    return indexMax;
}

...

```

# Създаване на “Шаблон на функция”

```
template <typename T>
int findIndexMax (T arr[], int arrSize)
{
    int indexMax = 0;
    for (int i = 1; i < arrSize; i++)
        if (arr[indexMax] < arr[i])
            indexMax = i;

    return indexMax;
}
```

# Използване на шаблона на функция

```

int main ()
{
    int arri[] = {1,5,6,7};
    cout << findIndexMax<int> (arri,4);

    double arrd[] = {2.1,17.5,6.0};
    cout << findIndexMax<double> (arrd,3);

    char arrc[] = "Hello";
    cout << findIndexMax<char> (arrc,5);

    char* arrstr[] = {"Hello", "World", "!"};
    cout << findIndexMax<char*> (arrstr,3); //!!!
}

```

```

template <typename T>
int findIndexMax
(T arr[], int arrSize)
{
    int indexMax = 0;
    for (int i = 1; i < arrSize; i++)
        if (arr[indexMax] < arr[i])
            indexMax = i;

    return indexMax;
}

```

- Конкретният тип трява да е съвместим с всички операции с него, които се прилагат в шаблона (в горния пример - < )!

# Още един пример: печатане на “всякакви” масиви

```
template <typename T>
void printArray (T arr[], int arrSize)
{
    cout << "{"
    for (int i = 0; i < arrSize - 1; i++)
        cout << arr[i] << ",";

    if (arrSize > 0) //no comma
        cout << arr[arrSize - 1];

    cout << "}";
}
```

## Още по-дълбока параметризация: функции като параметри

# Пример за еднотипни функции

```
int findIndexMax  (int arr[], int arrSize)
{
    int index = 0;
    for (int i = 1; i < arrSize; i++)
        if (arr[index] < arr[i])
            index = i;

    return index;
}

int findIndexMin  (int arr[], int arrSize)
{
    int index = 0;
    for (int i = 1; i < arrSize; i++)
        if (arr[index] > arr[i])
            index = i;

    return index;
}
```

# Функции вместо операторите < и >

```
bool compareGt (int a, int b)
{
    return a > b;
}
bool compareLt (int a, int b)
{
    return a < b;
}

int findIndexMax
    (int arr[], int arrSize)
{
    int index = 0;
    for (int i = 1; i < arrSize; i++)
        if (compareLt (arr[index],arr[i]))
            index = i;

    return index;
}

int findIndexMin
    (int arr[], int arrSize)
{
    int index = 0;
    for (int i = 1; i < arrSize; i++)
        if (compareGt (arr[index],arr[i]))
            index = i;

    return index;
}
```

# Функциите имат тип

*comparator : int × int → bool*

```
bool compareGt (int a, int b)
{return a > b;}
bool compareLt (int a, int b)
{return a < b;}
```

*ptrFn : T<sub>1</sub> × T<sub>2</sub> × ... × T<sub>k</sub> → T<sub>res</sub>*

```
int main (){
    //variable definition:
    //pComparator
    bool (*pComparator) (int ,int );

    //pointer assignment
    pComparator = compareLt;
    cout << pComparator (1,2);

    pComparator = compareGt;
    cout << pComparator (1,2);
}
```

T<sub>res</sub> (\*ptrFn) (T<sub>1</sub>, T<sub>2</sub>, ..., T<sub>k</sub>);

# Функциите имат тип

*comparator : int × int → bool*

```
bool compareGt (int a, int b)
{return a > b;}
bool compareLt (int a, int b)
{return a < b;}
```

*ptrFn : T<sub>1</sub> × T<sub>2</sub> × ... × T<sub>k</sub> → T<sub>res</sub>*

```
int main (){
    //variable definition:
    //pComparator
    bool (*pComparator) (int,int);

    //pointer assignment
    pComparator = compareLt;
    cout << pComparator (1,2);

    pComparator = compareGt;
    cout << pComparator (1,2);
}
```

T<sub>res</sub> (\*ptrFn) (T<sub>1</sub>, T<sub>2</sub>, ..., T<sub>k</sub>);

# Функциите имат тип

*comparator : int × int → bool*

```
bool compareGt (int a, int b)
{return a > b;}
bool compareLt (int a, int b)
{return a < b;}
```

*ptrFn : T<sub>1</sub> × T<sub>2</sub> × ... × T<sub>k</sub> → T<sub>res</sub>*

```
int main (){
    //variable definition:
    //pComparator
    bool (*pComparator) (int,int);

    //pointer assignment
    pComparator = compareLt;
    cout << pComparator (1,2);

    pComparator = compareGt;
    cout << pComparator (1,2);
}
```

T<sub>res</sub> (\*ptrFn) (T<sub>1</sub>, T<sub>2</sub>, ..., T<sub>k</sub>);

# Функциите имат тип

*comparator : int × int → bool*

```
bool compareGt (int a, int b)
{return a > b;}
bool compareLt (int a, int b)
{return a < b;}
```

*ptrFn : T<sub>1</sub> × T<sub>2</sub> × ... × T<sub>k</sub> → T<sub>res</sub>*

```
int main (){
    //variable definition:
    //pComparator
    bool (*pComparator) (int,int);

    //pointer assignment
    pComparator = compareLt;
    cout << pComparator (1,2);

    pComparator = compareGt;
    cout << pComparator (1,2);
}
```

T<sub>res</sub> (\*ptrFn) (T<sub>1</sub>,T<sub>2</sub>,...,T<sub>k</sub>);

# Предаване на функции като параметри

```
int findExtremum
    (int arr[],
     int arrSize,
     bool (*pComparator)(int ,int ))
{
    int index = 0;
    for (int i = 1; i < arrSize; i++)
        if (pComparator (arr[index],arr[i]))
            index = i;

    return index;
}

bool compareGt (int a, int b)
{return a > b;}
bool compareLt (int a, int b)
{return a < b;}
```

# Предаване на функции като параметри

```
void sort (int arr[],  
          int arrSize,  
          bool (*pComparator)(int, int))  
{  
    for (int i = 0; i < arrSize - 1; i++)  
    {  
        //find subarray extremum and  
        //swap with a[i]  
        swap (arr[i],  
              arr[i+findExtremum(arr+i,  
                                 arrSize-i,  
                                 pComparator)]);  
    }  
}
```

# Предаване на функции като параметри

```

int main ()
{
    int arr[] = {1,7,3,5,2,3,2,4};

    sort (arr,8,compareLt);
    printArray (arr,8);

    sort (arr,8,compareGt);
    printArray (arr,8);

    return 0;
}

bool compareGt (int a, int b)
{return a > b;}
bool compareLt (int a, int b)
{return a < b;}

int findExtremum
(
    int arr[],
    int arrSize,
    bool (*pComparator)(int,int))
{
    int indexMax = 0;
    for (int i = 1; i < arrSize; i++)
        if (pComparator (arr[indexMax],arr[i]))
            indexMax = i;
    return indexMax;
}

void sort (int arr[],
           int arrSize,
           bool (*pComparator)(int,int))
{
    for (int i = 0; i < arrSize-1; i++)
    {
        swap (arr[i],
              arr[i+findExtremum(arr+i,
                                   arrSize-i,
                                   pComparator)]);
    }
}

```

